

MR+A-6

AUG 2 1956

US DOE ARCHIVES
326 U.S. ATOMIC ENERGY
COMMISSION

Collection SECRETARIAT

Box 1263

Folder MR+A-7 Redwing Vol.3

CLASSIFICATION BY OC DATED
BY 26 JUN 74 DATE 3 JUN 73

MEMORANDUM FOR Mr. Stevens
Mr. Murray
Dr. Libby
Mr. Vance
Mr. Fields

Subject: FALL-OUT FROM KIWI

At Commission Meeting 1718 on July 24, 1956, the General Manager reported on fall-out occurring at Parry and Kaiwetek from the KIWI shot. Dr. Libby requested that information on whether clean up techniques could be practiced in the contaminated areas and the results. Based on this I teletyped Mr. Gordon Felt, who was still at the Proving Ground, asking the following:

- a. Was any decontamination attempted and how effective was this?
- b. From the heavy rainstorms during the period is it possible to determine any washdown effect therefrom and to establish any quantitative relationship?
- c. Is there quantitative evidence with respect to the reduction of exposure incident to taking cover in the type shelters available there?

To these questions Mr. Felt replied as follows:

- a. Decontamination was not attempted.
- b. It is difficult to assign quantitative numbers to washdown effect. Such effect was noticeable, however, inasmuch as regions adjacent to peaked-roof buildings and tents read almost twice as high as clear but un-stabilized areas. Puddles of water, especially on Kaiwetek runway and parking areas, showed very high concentration of activity up to 10 times general area level. Until early morning of 26 July, local time,

CONFIRMED TO BE UNCLASSIFIED

BY AUTHORITY OF DOE/OC

Carl Wilson 1/26/84
REVIEWED BY

By T Femer
3/19/86

COPY FOR SECRETARIAT

rain were not heavy enough to produce washdown of the general area. At that time high winds and rain falling at several inches per hour for about four hours reduced the general background approximately half.

- c. Film badges used as controls were located about three feet inside an aluminum building and showed reduction to about 60 percent of outside integrated dose. Dose rate survey meters indicated about 90 percent of outside rate at positions greater than eight feet from interior of building walls. Film badges worn by office workers show a dose of about 60 percent of outside integrated dose. People working outside most of the day accumulated about 90 percent of the outside integrated dose.
- d. Though we did not attempt decontamination we believe local areas could have been cleared where necessary by extensive hoeing. Such methods presuppose appreciably better drainage than we have here. The technique should work well in cities but would be less effective in suburban areas. In suburban and rural areas our experience both here and in Nevada suggests that surface grading is a very effective method of local decontamination. We intend to clear Perry Island living and working areas by this method in order to reduce long time doses to AEC and contractor personnel who will remain here.
- e. We believe protection afforded by buildings resulted primarily from distance effects since tents, though less well documented, showed similar trend.

By separate teletype Dr. Felt reported the following:

Department of Energy

Historian's Office

ARCHIVES

- a. Maximum readings on Perry and Eniwetok were about 170 mr at 26 hours after the shot. No maximum was recorded on Japtan or other local islands and no fall-out was observed at weather station islands and Enyu (Nikini). No fall-out was reported on Rongelap.

D-A
**SECRET
SACRED**

- 3 -

- b. Readings were spotty on Parry due to the fact that the fall-out occurred with rain and high surface winds. Spottiness increased after fall-out ceased owing to subsequent rain washings.
- c. The ships Ainsworth, Curtiss and Bruteen ran into fall-out traveling from Bikini to Eniwetok. The Curtiss sailed with ship buttoned up and activated washdown equipment every 15 minutes all during night as it stood off Parry Island. By noon, Sunday, local time (approximately 30 hours after the shot) background was reduced to about 5 mr.
- d. Rain was frequent during the first night. The main effect was to keep deposition rate even with decay so that readings held even for approximately 6 to 8 hours before beginning to drop.

The teletypes from which the above information was extracted were distributed separately to each Commissioner, to Los Alamos Scientific Laboratory and Livermore, to Commander, Joint Task Force SEVEN and to Armed Forces Special Weapons Project when received. I am requesting that the Albuquerque Operations Office keep us informed of the results from any scraping or other decontaminating effort.

Department of Energy
Historian's Office
ARCHIVES
Alfred D. Starbird
Brigadier General, USA
Director of Military Application

CONFIDENTIAL
Distribution Control stamp almost A.R.U.
Distribution by 2 units to serial
2263 9 300
M.A. 10/16/89